

### Brake disc



**183 521 1017/PD**

#### Notes

Bolt Hole Circle Ø [mm]	112
Brake Disc Thickness [mm]	22
Centering Diameter [mm]	68
Height [mm]	46,5
Minimum thickness [mm]	20
Number of Holes	5
Outer diameter [mm]	280
Wheel Bolt Bore Ø [mm]	15,3
	High-carbon
	Vented
	with screws
	Zink flake coated



#### New applications

AUDI A4 (8H7) (04/02-03/09)

### Brake disc

**315 521 3011**

#### Notes

	Front Axle
Bolt Hole Circle Ø [mm]	120
Brake Disc Thickness [mm]	22
Centering Diameter [mm]	79
Height [mm]	51,6
Minimum thickness [mm]	20,4
Number of Holes	5
Outer diameter [mm]	286
Wheel Bolt Bore Ø [mm]	14,5
	Vented



#### New applications

BMW 3 (E36) (09/90-08/00)  
BMW 3 (E46) (02/98-12/07)

BMW Z3 (E36/7, E36/8) (10/95-06/03)  
BMW Z4 (E85) (02/03--)

### Brake disc

**315 521 3020**

#### Notes

	Front Axle
Bolt Hole Circle Ø [mm]	120
Brake Disc Thickness [mm]	22
Centering Diameter [mm]	79
Height [mm]	51,6
Minimum thickness [mm]	20,4
Number of Holes	5
Outer diameter [mm]	300
Wheel Bolt Bore Ø [mm]	14,5
	Vented



#### New applications

BMW 3 (E46) (02/98-12/07)  
BMW Z3 (E36/7, E36/8) (10/95-06/03)

BMW Z4 (E85) (02/03--)

### Brake disc



**383 521 3011/PD**

#### Notes

	Front Axle
Bolt Hole Circle Ø [mm]	120
Brake Disc Thickness [mm]	22
Centering Diameter [mm]	79
Height [mm]	51,6
Minimum thickness [mm]	20,4
Number of Holes	5
Outer diameter [mm]	286
Wheel Bolt Bore Ø [mm]	14,5
	High-carbon
	Vented
	with screws
	Zink flake coated



#### New applications

BMW 3 (E36) (09/90-08/00)  
BMW 3 (E46) (02/98-12/07)

BMW Z3 (E36/7, E36/8) (10/95-06/03)  
BMW Z4 (E85) (02/03--)

### Brake disc



**383 521 3020/PD**

#### Notes

	Front Axle
Bolt Hole Circle Ø [mm]	120
Brake Disc Thickness [mm]	22
Centering Diameter [mm]	79
Height [mm]	51,6
Minimum thickness [mm]	20,4
Number of Holes	5
Outer diameter [mm]	300
Wheel Bolt Bore Ø [mm]	14,5
	High-carbon
	Vented
	with screws
	Zink flake coated



#### New applications

BMW 3 (E46) (02/98-12/07)  
BMW Z3 (E36/7, E36/8) (10/95-06/03)

BMW Z4 (E85) (02/03--)

### Brake hose

**714 525 0014**

#### Notes

Length [mm]	345
Outer thread 1 [mm]	M10x1
Outer thread 2 [mm]	M10x1
Required quantity	2

#### New references

FORD	6 125 634
------	-----------




#### New applications

FORD Fiesta IV / Puma (08/95-06/02)  
FORD Scorpio I (04/85-12/94)


FORD Sierra (08/82-03/93)

### Brake pad set

 **025 219 4519-1/PD**

#### Notes

Brake System	Front Axle
Height [mm]	TRW
Number of wear indicators [per axle]	69,4
Quality	2
Thickness [mm]	PREMIUM
Warning Contact Length [mm]	19,6
Width [mm]	196
	118,9
	incl. wear warning contact with anti-squeak plate



#### New applications


AUDI A4 (8H7) (04/02-03/09)

### Brake pad set

**025 219 4519/W**

#### Notes

Brake System	Front Axle
Height [mm]	TRW
Number of wear indicators [per axle]	69,4
Thickness [mm]	2
Warning Contact Length [mm]	19,6
Width [mm]	196
	118,9
	incl. wear warning contact with anti-squeak plate



#### New applications


AUDI A4 (8H7) (04/02-03/09)

### Brake pad set

**025 220 3517**

#### Notes

Brake System	Front Axle
Height [mm]	ATE
Number of wear indicators [per axle]	62,4
Thickness [mm]	1
Warning Contact Length [mm]	17,4
Width [mm]	155
	146,1
	incl. wear warning contact
	with anti-squeak plate



#### New applications


AUDI A3 (8V1, 8VS, 8V7, 8PA) (04/12--)

### Brake pad set

**025 241 9118**

#### Notes

Brake System	Front Axle
Height [mm]	TRW
Thickness [mm]	58,7
Width [mm]	18,2
	162,6
	prepared for wear indicator
	with anti-squeak plate



#### New applications

LAND ROVER Discovery III (07/04-09/09)  
LAND ROVER Discovery IV (09/09--)

LAND ROVER Range Rover III (03/02-08/12)  
LAND ROVER Range Rover Sport (02/05--)

### Brake pad set


**025 250 9616/W**

#### Notes

Brake System	Rear Axle
Height [mm]	ATE
Thickness [mm]	42,7
Width [mm]	16,1
	116,6
	with accessories
	with acoustic wear warning
	with anti-squeak plate

#### New references

CHEVROLET	13411380
	13411383
GENERAL MOTORS	13473427
	13473428
OPEL	16 05 294
	16 05 296



#### New applications

CHEVROLET Aveo II (03/11--)	VAUXHALL Astra Mk V (01/04-11/11)
CHEVROLET Trax (12/12--)	VAUXHALL Cascada (02/13--)
OPEL Cascada (03/13--)	VAUXHALL Mokka (06/12--)
OPEL Mokka (06/12--)	

### Sensor, camshaft position

**314 899 0069**

#### Notes

Cable Length [mm]	355
Fitting Depth [mm]	28
Number of Poles	3
Operating voltage [V]	12
	Active sensor with seal



#### New applications

LAND ROVER Discovery III (07/04-09/09)


LAND ROVER Discovery IV (09/09--)

### Air filter

**112 321 0031**

#### Notes

Height [mm]	30,5
Length [mm]	270
Width [mm]	190
	Filter Insert



#### New applications

AUDI A1 (8X1, 8XA) (05/10--)

### Oil filter

**100 322 0021**

#### Notes

Bypass Valve Opening Pressure [bar]	2,5
Height [mm]	78
Outer diameter [mm]	77
Thread Size	3/4"-16 UNF-1B
	Screw-on Filter with one anti-return valve



#### New applications

AUDI A1 (8X1, 8XA) (05/10--)

### Oil filter

**16-14 322 0000**

#### Notes

Bypass Valve Opening Pressure [bar]	1
Height [mm]	50,6
Outer diameter [mm]	76
Thread Size	M20x1,5
	Screw-on Filter



#### New applications

ALFA ROMEO 147 (11/00-03/10)



### Ball joint

**316 010 0011**

#### Notes

Thread Size

Front Axle Left  
Front Axle Right  
M14x1,5  
with accessories



#### New applications

BMW X3 (E83) (01/04-12/08)

### Control arm

**416 050 0000**

#### Notes

Left  
Right  
Aluminium  
Control Arm  
not adjustable  
with ball joint  
with rubber mounting



#### New applications

PORSCHE Boxster (987) (11/04-12/11)

### Shock absorber

**28-26 725 0002**

#### Notes

Rear Axle  
Bottom eye  
Gas Pressure  
Top pin  
Twin-Tube



#### New applications

KIA Picanto II (05/11--)

### Stabilizer link



**116 060 0000/HD**

#### Notes

	Reinforced Version
	Front Axle Left
	Front Axle Right
Length [mm]	270
Thread Measurement 1	M10x1,5
Thread Measurement 2	M10x1,5
	Coupling Rod with spanner attachment



#### New applications

VW Spacefox (5Z6, 5Z7)

### Stabilizer link



**116 060 0020/HD**

#### Notes

	Reinforced Version
	Front Axle Left
	Front Axle Right
Length [mm]	335
Thread Measurement 1	M12X1,5
Thread Measurement 2	M12X1,5
	Coupling Rod with spanner attachment



#### New applications

VW Jetta City (09/06-12/09)

### Stabilizer link



**116 060 0021/HD**

#### Notes

	Reinforced Version
	Rear Axle Left
Inner diameter 1 [mm]	12
Length [mm]	200
Paired article numbers	116 060 0022/HD
Thread Measurement 1	M12x1,5
	Suspension Rod
	with accessories
	with spanner attachment



#### New applications

AUDI Q7 (4M) (06/15--)

### Stabilizer link



**116 060 0022/HD**

#### Notes

	Reinforced Version
	Rear Axle Right
Length [mm]	250
Paired article numbers	116 060 0021/HD
Thread Measurement 1	M12X1,5
	Suspension Rod
	with accessories
	with spanner attachment



#### New applications

AUDI Q7 (4M) (06/15--)

### Stabilizer link

**116 060 0023**

#### Notes

	Rear Axle Left
	Rear Axle Right
Inner diameter [mm]	10
Length [mm]	95
Thread Measurement 1	M10x1,5
	Coupling Rod



#### New applications

VW Passat (A32) (04/11-12/14)

### Stabilizer link

**116 060 0023/S**

#### Notes

Inner diameter [mm]  
Length [mm]  
Thread Measurement 1  
Thread Measurement 2

Rear Axle Left  
Rear Axle Right  
10  
95  
M10x1,5  
M10x1,5  
Coupling Rod  
Kit  
with accessories



#### New applications

VW Passat (A32) (04/11-12/14)

### Stabilizer link



**44-16 060 0000/HD**

#### Notes

Length [mm]  
Thread Measurement 1  
Thread Measurement 2

Reinforced Version  
Replace in pairs only  
Front Axle Left  
Front Axle Right  
310  
M12X1,5  
M12X1,5  
Coupling Rod  
with spanner attachment



#### New applications

VW Routan (09/08-12/11)

### Strut mount

**100 513 0010**

#### Notes

Rear Axle  
Round  
without ball bearing



#### New applications

AUDI A1 (8X1, 8XA) (05/10--)  
AUDI A3 (8P1, 8PA) (05/03-08/12)  
AUDI Q3 (8U) (06/11--)  
AUDI TT (8J3, 8J9) (08/06-06/10)  
SEAT Alhambra II (710) (06/10-05/11)  
SEAT Leon / Toledo / Altea (1P1, 5P2, 5P5) (03/04-05/10)  
SKODA Octavia II (1Z\_) (02/04-12/10)  
SKODA Superb II (3T) (03/08-11/10)  
SKODA Yeti (5L) (05/09--)

VW CC (11/11--)  
VW Golf V (1K1, 1K5, 5M1) (10/03-05/09)  
VW Golf VI (5K1, 517, AJ5) (10/08-11/13)  
VW Jetta IV (162) (04/10--)  
VW Passat (362, 365) (08/10--)  
VW Passat (3C\_) (03/05-10/11)  
VW Scirocco (137) (05/08-05/11)  
VW Tiguan (09/07-08/09)  
VW Touran (1T3) (05/10-01/13)

### Sway bar



**100 653 0009/HD**

#### Notes

Stabiliser Diameter [mm]

Front Axle  
21,7  
with clamps  
with rubber mounting



#### New applications

SKODA Octavia II (1Z\_) (02/04-12/10)